


BESKRIVNING

CHRYSO®ScreedFinish EBA 50 is a water based evaporation barrier agent, ready to use & specifically designed to enhance CHRYSO® Cemfloor & Mobicem screeds curing process. Because it forms a protective film on the screed surface, CHRYSO®ScreedFinish EBA 50 slows down drastically the screed desiccation. It allows for screed hydration enhancement, reduces the risk for plastic shrinkage induced cracking or surface delamination and dusting. After setting, the screed surface abrasion resistance is also improved.

CHRYSO®ScreedFinish EBA 50 includes a temporary white tracer which allows to identify easily the surface treated. The white color fades once the product is dry. By nature, CHRYSO®ScreedFinish EBA 50 doesn't require any removal (sanding or grinding) if the adhesion tests exhibit satisfactory results (see flooring solution manufacturer's recommendations). Due to its water-based technology, CHRYSO®ScreedFinish EBA 50 is user and environment friendly.



ANVÄNDNINGSOMRÅDEN

- Cemfloor or Mobicem screeds

EGENSKAPER

Karaktär	liquid
Färg	White
Hållbarhet	12 månader
Densitet	1,000 ± 0,010
pH	9,00 ± 0,50

ANVÄNDNINGSMETOD

This product is ready to use. Spray on top of the screed immediately after the dappling brush or bar has been used so that the screed is protected against desiccation as soon as possible. We recommend a spraying equipment with flat spray nozzle and a minimum pressure of 3 bars (45 psi). Apply CHRYSO®ScreedFinish EBA 50 evenly on the screed ($100 - 150 \text{ ml/m}^2$) in order to obtain a uniform white color surface. A 2 crossed spray passes process is recommended to avoid any application gap. Rinse and wash the spraying equipment with water before the product dries up.

Dosering:

100 to 150 ml/m²

1L = ~7 to 10 m²

FÖRSIKTIGHETSÅTGÄRDER

- Stir the product before use.
- Protect from frost.
- Avoid prolonged exposure to high temperatures.

SÄKERHET

Innan användning, läs igenom säkerhetsdatabladet på vår hemsida www.chryso.se.